



OptiFuel

Precision and Portability in a
Top of the Line FTIR Fuel Analyzer

- ⊕ Superior performance and ruggedness
- ⊕ Expert service and support worldwide
- ⊕ Unmatched warranty on critical components


ACCURATE, EASY AND RELIABLE FUEL ANALYSIS

For more than 20 years, PAC has been at the forefront of infrared (IR) fuel analysis with its PetroSpec products. Now we are combining the best of our GS PPA, TD PPA and QuickSpec capabilities into one analyzer and adding the latest FTIR technology into the most robust fuel analyzer in the market.

The user-friendly system allows the operator to measure many properties at once with a simple touch of a button, using free factory calibration models. Users can customize the models with local samples in a few seconds. These custom models can easily be cloned to all your OptiFuels, even remotely, if necessary.

GLOBAL SUPPORT

- 🌐 Extensive support network through our offices and over 140 distributors worldwide
- 🌐 ISO 9001 compliant manufacturing facility and service repair centers
- 🌐 Skilled certified service technicians



PAC Offices

Distributors

KEY FEATURES



EXTENDED WARRANTY

- 1-year standard system warranty
- 10-year optics warranty on the full range, laser-referenced Michelson interferometer
- 5-year warranty on the IR light source



SUPERIOR PERFORMANCE

- Excellent correlation to a wide range of ASTM, EN, and ISO standard
- Calibration lasts for years
- High resolution wide range FTIR - ATR single flow cell
- Measure multiple parameters at once



RELIABLE DESIGN

- Modern temperature-controlled laser referenced Michelson interferometer
- Humidity and vibration resistant ZnSe mirrors, beam splitters, and non-moving sample cell




LOW COST OF OWNERSHIP

- One instrument measures all types of samples without the need for extra hardware
- On-site, fast, and minimal maintenance
- Low cost of consumables

USER-FRIENDLY INTERFACE

- Intuitive interface requires minimal user training
- Large touch-screen allows easy navigation
- On-system, one-button-push model update with regional samples
- One-step, rapid calibration transfer and cloning
- Easy-to-use LIMS connectivity



INCLUDED PARAMETERS

Every OptiFuel comes with an extensive set of calibration models built using hundreds of real-life samples of gasoline and diesel from all over the globe, following ASTM E1655. These calibration ranges are based on current factory models, but they all can easily be expanded in the field. Calibrations can easily be cloned and transferred to additional units.

GASOLINE

Properties ¹	Range ²
Research Octane Number (RON)	90-102
Motor Octane Number (MON)	81-93
Anti Knock Index (AKI)	85-98
Distillation Points	
IBP	25-47°C (77-116°F)
T10	38-67°C (101-152°F)
T50	67-117°C (158-242°F)
T90	124-178°C (255-353°F)
FBP	171-221°C (339-430°F)
Evaporation Points	
E70	11-53% (v/v)
E100	32-75% (v/v)
E150	79-97% (v/v)
E180	90-99% (v/v)
E200	29-73% (v/v)
E300	77-99% (v/v)
DVPE	42-105 kPa
Driveability Index	380-665
Vapour Lock Index	500-1450
MTBE	0-21% (m/m)
ETBE	0-21% (m/m)
TAME	0-21% (m/m)
Methanol	0-6.5% (m/m)
Ethanol	0-14% (m/m)
DIPE	0-21% (m/m)
tert-Butanol	0-15% (m/m)
Total Oxygen	0-24% (m/m)
Olefins	0.3-27% (v/v)
Total Aromatics	5-45% (v/v)
Aromatics C7	0.8-18% (v/v)
Aromatics C8	0.5-16% (v/v)
Benzene	0-5.5% (v/v)
Benzene Plus	0-2.27% (v/v)
VOC	1250-1560 mg/mi
VOC Performance	-6-16%
Saturates	0-95% (v/v)
Density	0.6-1.2 g/cm3

DIESEL


Properties ¹	Range ²
FAME (low to high concentration)	0-100% (v/v)
Cetane Number	41-67
Cetane Index	43-65
Viscosity	
Kinematic Viscosity	1.6-4.4 mm ² /s
Dynamic Viscosity	1-5.3 cP
Distillation Points	
IBP	109-212°C (228-413°F)
T5	153-241°C (308-466°F)
T10	164-251°C (328-483°F)
T20	182-262°C (359-504°F)
T30	197-275°C (386-527°F)
T40	210-290°C (411-554°F)
T50	225-304°C (437-579°F)
T60	237-315°C (458-599°F)
T70	250-342°C (482-647°F)
T80	261-366°C (501-690°F)
T90	273-390°C (523-735°F)
T95	284-401°C (543-753°F)
FBP	301-403°C (574-757°F)
Evaporation Points	
E250	10-72% (v/v)
E350	75-99% (v/v)
Aromatics	
Mono Aromatics	1-31% (m/m)
Di Aromatics	0-13% (m/m)
Tri+ Aromatics	0-2.2% (m/m)
Total Aromatics	1.1-46% (m/m)
Polycyclic Aromatics	0-15% (m/m)
Density	0.6-1.2 g/cm ³

JET FUEL

Properties ¹	Range ²
Density (built-in U-tube cell)	0.6 - 1.2 g/cm ³

DENSITY MODULE

An ASTM compliant Oscillating tube density module, capable of measuring from 0.6 g/cm^3 to 1.2 g/cm^3 , is integrated in each OptiFuel to provide direct density reading. Per ASTM D1250-04 algorithm, densities of hydrocarbon samples can be reported at 15°C from 0.6 to 1.2 g/cm^3 . This eliminates the need for an external density meter.



ROAD-TESTED FOR MOBILE APPLICATIONS


OptiFuel comes in a rugged, yet elegant, design with a friendly user interface, which makes it ideal for refineries, pipelines, terminals, and mobile labs.

We used only the best materials to ensure it delivers unmatched performance in any application, and tested through intense shock, vibration and drop, per applicable IEC procedures.



Mobile Lab is enclosed climate controlled lab with ambient temperature and humidity within product specification to obtain desired performance.

MOBILE ACCESSORY PACKAGE



**Anti-vibration
Platform**



**High-performance
lithium ion battery with
power supply**



**Vehicle
Adapter**

NOTE: OptiFuel runs for over 5 uninterrupted hours on just the battery pack, untethered from a vehicle, or an external power outlet.

COMPLETE CONNECTIVITY

Easily connect your OptiFuel to your network printer or LIMS system. You can also digitally clone your OptiFuel with a USB drive.



METHOD-APPROVED

Compliance	Correlation		Method Applications
<ul style="list-style-type: none"> ● ASTM D6277 ● ASTM D5845 ● ASTM D7371 ● ASTM D7777 ● ISO 15212 	<ul style="list-style-type: none"> ● ASTM D2699 ● ASTM D2700 ● ASTM D5191 ● ASTM D86 ● ASTM D6839 ● ASTM D613 ● ASTM D4737A ● ASTM D445 	<ul style="list-style-type: none"> ● EN ISO 5164 ● EN ISO 5163 ● EN 13016/1 ● EN ISO 3405 ● EN ISO 22854 ● EN ISO 5165 ● EN ISO 4264 ● EN 3104 ● EN 12916 	<p>Correlation Results for Methods in Specifications:</p> <ul style="list-style-type: none"> ● ASTM D975 ● ASTM D4814 ● EN 228 ● EN 590

TECHNICAL SPECIFICATIONS

Spectrometer Type	FTIR Michelson Interferometer		
Standard Test Methods	Compliance - ASTM D6277, ASTM D5845, ASTM D7371, ASTM D7777, ISO 15212 Correlation - ASTM D2699, ASTM D2700, ASTM D5191, ASTM D86, ASTM D6839, ASTM D613, ASTM D4737A, ASTM D445, EN ISO 5164, EN ISO 5163, EN 13016/1, EN ISO 3405, EN ISO 22854, EN ISO 5165, EN ISO 4264, EN 3104, EN 12916 Method Applications - Correlation Results for Methods in Specifications: ASTM D975, ASTM D4814, EN 228, EN 590		
Mirror Design	Friction-free, vibration resistant, cube corner mirror		
Mirror and Beam Splitter	Humidity resistant ZnSe		
Density Measurement	Oscillating tube		
Units of Measurement	%m, %v		
Scan Range	550 - 4000 cm ⁻¹		
Spectral Resolution (max.)	2 cm ⁻¹		
Measurement Time	30 seconds		
Sample Introduction	From air pressure		
Sample Volume	20-30 ml depending on sample type		
Calibration Model	Factory calibrated with matrix of several hundred global fuels (analyzed by SGS)		
Regional Calibration Model Update	Yes		
Cleaning	Solvent (≥ 99.9% Toluene, >99% Hexane)		
Operating Temperature	15°C to 35°C	Storage Temperature	-40°C to +85°C
Humidity (Non-Condensing)	0% to 80% RH*		
Leak Test	Automatic		
Filter Replacement Monitor	Automatic		
Fume Sensor	Yes	Real-time Safety Monitoring	Yes
Display	7" color touch screen		
Interface	3x USB - 1x Ethernet		
Instrument Memory	100,000 test results		
Power Requirements	110V to 230V - 50/60 Hz, 60 W. 24V battery pack option available, connectable to 12V.		
Dimensions & Weight	8.5" x 14" x 16" 22 x 36 x 41 cm (W x H x D) 32 lbs (14.5 kg)		
Packaging	24" x 24" x 24" 61x 61 x 61 cm (W x H x D) - 56lbs (25.4 kg)		
Certifications	ISO 9001:2015, CE, ROHS II		

*Must maintain instrument internal humidity less than 50% via regular desiccant change. Continuing research and development may result in specifications or appearance changes at any time.



ABOUT PAC

PAC develops advanced instrumentation for lab and process applications based on strong Analytical Expertise that ensures Optimal Performance for our customers. Our analyzers help our customers meet complex industry challenges by providing a low cost of ownership, safe operation, high performance with fast, accurate, and actionable results, high uptime through reliable instrumentation, and compliance with standard methods.

HEADQUARTERS

PAC LP | 8824 Fallbrook Drive | Houston, Texas 77064 | USA
 T: +1 800.444.8378 | F: +1 281.580.0719

Our solutions are from industry-leading brands: AC Analytical Controls, Advanced Sensors, Alcor, Antek, Herzog, ISL, Cambridge Viscosity, Phase Technology, PSPI, and PetroSpec. We are committed to delivering superior and local customer service worldwide with 16 office locations and a network of over 50 distributors. PAC operates as a unit of Roper Technologies, Inc., a diversified technology company and a constituent of S&P 500, Fortune 1000, and Russell 1000 indices.



Contact us for more details.
 Visit our website to find the PAC representative closest to you.

